
WUHAN KING	PLASTIC	COMPOSITE	MATERIAL	СО.,	LTD
WUHAN KING PLASTIC COMPOSITE MATERIAL CO., MATERIAL SPECIFICATION					

MATERIAL SPECIFICATION								
TITLE	NO. :	ISSUE:	DATE:	MAY, 2009				
PLASTIC COATED		1						
STEEL TAPE	WHSJ-MS-1020		PAGE:	1/1				

1. SCOPE:

This specification covers the requirements for steel tape with a film of specially compounded polyethylene copolymer resin fused to one or both side. Steel tape will be used as a shield in Cables.

2. DESCRIPTION:



XX=02: Steel tape should be copolymer coated on two sides

ITEM	PROPERTY	Test Method	Unit	Value
1	Composition as per	DIN 1712	_	_
2	Tensile strength	ASTM A-370	N/mm ²	300-400N/mm2
3	Elogation	ASTM A-370	c / ₀	≥15%
4	Thickness of coating		mm	0.058 ± 0.013
5	Steel thickness		mm	0.15 ± 0.01
6	Overall thickness		mm	0.25
7	Peel strength of coating	ASTM A-370	N/CM	≥6.1N/CM

3. PAD DIMENSIONS:

-Tape length -Tape width -Inside dial of pad 2150 ± 50 m as required (16-1000MM) 150,400,500mm

4. PACKING:

As required of the customer